



Actros

Model	1836 - 1844 LS	2636 - 2644, L, LS & S, 2648 - 2660 LS & S	3341 - 3348 A	3241 - 3248, L, 4141 - 4144 B	4141 - 4148 AK
Configuration	4x2	6x4	6x6	8x4	8x8
Engine	11.9 litre V6 turbocharged with intercooling, 15.9 litre V8 turbocharged with intercooling (not available with all models)				
Power	360 - 598 hp (265 - 440 kW) @ 1,800 rpm				
Torque	1,850 - 2,800 Nm (1,365 - 2,065 lbf·ft) @ 1,080 rpm				
GVM kg	16,000 - 18,000	26,000	33,000 - 40,000	32,000 - 48,000	41,000 - 48,000
Tare kg (+/-3%)	From 6,250	From 7,860	From 10,095	From 9,750	From 11,670
GCM kg	55,000	55,000 - 90,000 [†]	70,000 [†]	55,000 - 70,000 [†]	70,000 [†]
Transmission	12 or 16-speed automated manual (2 pedal), 16-speed semi-automated manual (3 pedal)				
Rear Axle	H6 hypoid 13,000 kg	H7 planetary 2 x 13,000 - 16,000 kg			
Rear Suspension	2 bag air 11,500 kg	8 bag air, 2 x 10,000 kg, 6-rod parabolic*, 2 x 9,500 kg		8 bag air 2 x 10,000 kg, 6-rod parabolic 2 x 9,500 - 18,000 kg	
Front Axle	VL4 7,500 kg	VL4 7,500 kg	AL7 7,500 - 9,000 kg	VL4 2 x 7,500 - 9,000 kg	AL7 9,000 kg
Front Suspension	parabolic 7,100 - 9,000 kg			parabolic 2 x 7,500 - 9,000 kg	