



Axor

Model	1833 L, LS, A	2533 L	2633
Configuration	4x2 / 4x4	6x2	6x4
Engine	7.2 litre in-line 6 turbocharged with intercooling		
Power	326 hp (240 kW) @ 2,200 rpm		
Torque	1300 Nm (960 lbft) @ 1,200 - 1,600 rpm		
GVM kg	16,000 - 18,000	25,500	26,000 - 27,500
Tare kg (+/-3%)	From 5,505	From 7,235	From 7,695
GCM kg	Up to 39,000		
Transmission	9-speed synchromesh manual, 16-speed automated manual (3-pedal)		
Rear Axle	H6 hypoid, 13,000 kg, H7 planetary, 13,000 kg	H6 hypoid, 13,000 kg, Tag axle T25, 10,000 kg	H7 planetary, 13,000 kg
Rear Suspension	2-4 bag air, 11,500 kg, 4 leaf parabolic, 11,500 kg	8 bag air, 2 x 10,000 kg	6-rod, parabolic* 2 x 9,500 kg
Front Axle	AL7 / VL4 7,500 kg		
Front Suspension	2 - 3 leaf parabolic 7,100 - 7,500 kg		

+ 6-rod mechanical 'Road Friendly' version available 2 x 10,000 kg.